

















Misting Sytem (Fog Machine) Full set

S/N	Product	Code	CLFM-025	CLFM-050	CLFM-050S	CLFM-100	CLFM-150	CLFM-200	
SPEC.	<div style="border: 1px solid orange; padding: 5px; display: inline-block;">CLFM-025, CLFM-050, CLFM-050S</div> 	Motor	DC With brush 120W/12V		DC brushless 120W/12V	AC 180W	AC 180W	AC 250W	
		Piston QTY	3						
		Pressure	70Bar/1000psi						
		Inlet water flow	0.25L/min	0.5L/min	Auto (max 0.5L/min)	1.0L/min	1.5L/min	2.0L/min	
		Max nozzle quantity (0.15mm)	8	16	16	30	40	60	
		Max cooling area	20m2	40m2	40m2	75m2	100m2	150m2	
		Motor RPM	600	1200	500-1300	1400	1400	1400	
		Maintains Hours	2000h	1000h	1000-2000h	800-1000h	800-1000h	800-1000h	
		Self priming	--	--	--	√	√	√	
		Motor over heat protection	√	√	√	√	√	√	
	Water lack protection	--	--	√	√	√	√		
	<div style="border: 1px solid orange; padding: 5px; display: inline-block;">CLFM-100, CLFM-150, CLFM-200</div> 	Electrical leakage protection	√	√	√	√	√	√	
		Maintains Auto warning	--	--	√	√	√	√	
		Working noise with pressure	52db	54db	52db	56db	56db	58db	
		Touck key	√	√	√	√	√	√	
		80Bar HP solenoid valve (anti drip)	--	--	√	√	√	√	
		Over pressure protection	√	√	√	√	√	√	
		Remote control	√	√	√	√	√	√	
		Simple timer	--	--	√	--	--	--	
		Mobile APP(advanced Timer)	--	--	--	√	√	√	
With pressure sensor (automatically save energy)		--	--	√	--	--	--		
Standard package	Inlet water filter system	 <ul style="list-style-type: none"> * 3m water pipe with faucet connector * 1pcs Machine quick fitting 	--	--	--	1	1	1	
		 <ul style="list-style-type: none"> * High quality water filter 	--	--	--	1	1	1	
		 <ul style="list-style-type: none"> * Simple water filter (with faucet connector) * 2m water pipe with machine fitting 	1	1	1	--	--	--	
	Top level nozzles	 <ul style="list-style-type: none"> * With SS304 filter * Body: H59 top level Brass with nickel plating * Better anti drip * Viton seal 	5	8	8	12	20	40	
	Quick fitting	 <ul style="list-style-type: none"> * Brass with nickel plating * One hole for 1 nozzle 	4	7	7	11	19	39	
	End fitting	 <ul style="list-style-type: none"> * Quick fitting and very easy installation * Never has water leakage 	1	1	1	1	1	1	

Misting Sytem (Fog Machine) Full set

S/N	Product	Code	CLFM-025	CLFM-050	CLFM-050S	CLFM-100	CLFM-150	CLFM-200
Standard package	Machine quick fitting 	* Connect machine and PA12 pipe	1	1	1	1	1	1
	Nylon PA12 pipe 	* Max working pressure: 100Bar * Material: PA Nylon 12 * Double cost, double life than PA 6 * Size: 6.35mm (1/4")	15m	25m	25m	5m	5m	5m
	Stainless steel pipe 	* 304 SS material * 750mm length	--	--	--	11	19	39
		* 250mm length (for corner)	--	--	--	7	7	7
	Pipe Hanger 	* SS 304 material	5	8	8	12	20	40
	L type connector 	* Brass with nickel plating * Quick fitting and very easy installation * Never has water leakage	--	--	--	4	4	4
	Pipe cutter 	* 20cm* 9cm big pipe cutter * Max can cut 4cm diameter pipe	1	1	1	1	1	1
	Pump oil syringe 	* To fill the pump oil	1	1	1	1	1	1
	User manual	* with Plastic film cover	1	1	1	1	1	1
	O-ring, oil seal, water seal for free	* For maintains(after 800 hours running); * With full set of water seal, oil seal and O-ring;	1 set	1 set	1 set	1 set	1 set	1 set
	Common carton package	* Common strong carton	1	1	1	--	--	--
Strong carton package 	* Very Strong package without Logo; * Cago can bear 80Kg weigt; * Color package	-	-	-	1	1	1	